

Technical Features





Maximum range
4 m



Heating type
Unheated



Casing [*]
Galvanised steel



Airflow / Length
5300 - 15900 m³/h
1 m to 3 m



Heating capacity
-



Inlet grille
Circular perforated



Fans
Centrifugal
5-speed



Control
Plug&Play Advanced PRO
+ IR remote control
(Optional Clever PRO)



Outlet lamellas
Aluminium, airfoil type
Adjustable 0-15° each side

RAL 9016 standard



Stainless steel



Other colors on request



[*] Customizable dimensions on request

FLY KXL is recommended to reduce the passage of insects across industrial service doors up to 4 meters high.

A robust and versatile insect control air curtain, provided with an extensor outlet kit to optimize the air outlet with the minimum turbulence at maximum speed. Works with double-inlet centrifugal fans driven by an external rotor motor and low noise level.

Elegant and timeless design, with large perforated inlet grille avoiding intensive maintenance.

Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m RJ11 cable and remote control. Optional: intelligent Clever PRO Control (automatic, programmable, modbus for PLC, timer, etc).

In case of outdoor installation, the air curtain must be adequately protected from the weather. In addition, the electrical connections of the air curtain must be housed in a watertight box and it is recommended to protect the cabinet with AQUA AERO paint or stainless steel (see options).



❄ UNHEATED

Model	Airflow m³/h	Ventilation power		Ventilation current		Noise Level (5 m) dB(A)	Weight kg
		230V~50Hz kW	230V~60Hz kW	230V~50Hz A	230V~60Hz A		
FLY KXL 1000 A	5300	1,40	1,84	6,00	8,26	65	82
FLY KXL 1500 A	7950	2,10	2,76	9,00	12,39	66	123
FLY KXL 2000 A	10600	2,80	3,68	12,00	16,52	67	165
FLY KXL 2500 A	13250	3,50	4,60	15,00	20,65	68	202
FLY KXL 3000 A	15900	4,20	5,52	18,00	24,78	69	243



Selection program

Dimensions



According to standard NSF-37-2012, the maximum installation height in **service doors** is the speed profile point at 8,14m/s plus 0,9m. So **FLY KXL can be used until 3,1m + 0,9m = 4,0m.**

Optional accessories

Supports and installation



Wall rail support
SPWR



Silentblock supports
SPANG-SIL / SLB



Suspension cables
SPCT

Control



ADVANCED PRO
✓ Included



IR Control
✓ Included



RJ11 Cable
✓ Included



CLEVER PRO

Sensors



Mechanical door contact
DC



Magnetical door contact
✓ Included



External Temperature
Sensor (Clever PRO)

CAD drawings, BIM files, installation manuals and other documentation

