



Characteristics



- Medium pressure blades, airfoil perfilled aluminium of high performance with regulable angle blade at rest
- Galvanized steel casing or painted, short "1" or long "2" execution
- Certified for 400°C/2h for CTICM no. 90-E-082
- Fixation flange in both sides that gives more stiffness
- Other executions: 2 speed Motors, EX anti-explosion execution, models for tunnels, models with variable blades angle, 100% reversibles
- Other accessories optional: silencers, overpressure shutters, etc.
- The models listed are of 9 blades. Also available with 3 or 6 blades and other motor powers (the motor is calculated depending on the point of work required)

Specifications

Model	Speed (rpm)	Exit Signal (V)
AXV 1000-9-4 - 11 kW 400°/2h	1440	60000
AXV 1000-9-4 - 22 kW 400°/2h	1440	78000
AXV 1000-9-4 - 4 kW 400°/2h	1440	30000
AXV 1000-9-4 - 5,5 kW 400°/2h	1440	42500
AXV 1000-9-4 - 7,5 kW 400°/2h	1440	52000
AXV 1000-9-6 - 1,1 kW 400°/2h	960	23000
AXV 1000-9-6 - 2,2 kW 400°/2h	960	35000
AXV 1000-9-6 - 4 kW 400°/2h	960	44000
AXV 1000-9-6 - 7,5 kW 400°/2h	960	54000
AXV 1250-9-4 - 15 kW 400°/2h	1440	73500
AXV 1250-9-4 - 22 kW 400°/2h	1440	91000
AXV 1250-9-4 - 37 kW 400°/2h	1440	128000
AXV 1250-9-4 - 55 kW 400°/2h	1440	153000
AXV 1250-9-6 - 15 kW 400°/2h	960	95000
AXV 1250-9-6 - 4 kW 400°/2h	960	44000
AXV 1250-9-6 - 7,5 kW 400°/2h	960	68000
AXV 1400-9-6 - 15 kW 400°/2h	960	108000
AXV 1400-9-6 - 30 kW 400°/2h	960	140000
AXV 1400-9-6 - 5,5 kW 400°/2h	960	62500
AXV 1400-9-6 - 7,5 kW 400°/2h	960	83000
AXV 1600-9-6 - 15 kW 400°/2h	960	118000
AXV 1600-9-6 - 30 kW 400°/2h	960	157000
AXV 1600-9-6 - 37 kW 400°/2h	960	185000
AXV 1600-9-6 - 7,5 kW 400°/2h	960	80000
AXV 400-9-4 - 0,37 kW 400°/2h	1440	5300
AXV 500-9-4 - 0,55 kW 400°/2h	1440	9800
AXV 500-9-6 - 0,37 kW 400°/2h	960	6600
AXV 560-9-4 - 0,55 kW 400°/2h	1440	11300
AXV 560-9-4 - 1,1 kW 400°/2h	1440	14000
AXV 560-9-6 - 0,37 kW 400°/2h	960	9600
AXV 630-9-4 - 0,37 kW 400°/2h	1440	11500
AXV 630-9-4 - 0,75 kW 400°/2h	1440	14700
AXV 630-9-4 - 1,5 kW 400°/2h	1440	18500
AXV 630-9-6 - 0,75 kW 400°/2h	960	13700
AXV 710-9-4 - 1,1 kW 400°/2h	1440	15000
AXV 710-9-4 - 2,2 kW 400°/2h	1440	21500
AXV 710-9-4 - 4 kW 400°/2h	1440	27000



Model	Speed (rpm)	Exit Signal (V)
AXV 710-9-6 - 0,37 kW 400°/2h	960	18000
AXV 710-9-6 - 1,1 kW 400°/2h	960	18000
AXV 800-9-4 - 2,2 kW 400°/2h	1440	22500
AXV 800-9-4 - 4 kW 400°/2h	1440	31000
AXV 800-9-4 - 7,5 kW 400°/2h	1440	40000
AXV 800-9-6 - 0,75 kW 400°/2h	960	17000
AXV 800-9-6 - 1,5 kW 400°/2h	960	22500
AXV 800-9-6 - 2,2 kW 400°/2h	960	26000
AXV 900-9-4 - 11 kW 400°/2h	1440	55000
AXV 900-9-4 - 2,2 kW 400°/2h	1440	24500
AXV 900-9-4 - 4 kW 400°/2h	1440	36500
AXV 900-9-4 - 7,5 kW 400°/2h	1440	47500
AXV 900-9-6 - 0,75 kW 400°/2h	960	20000
AXV 900-9-6 - 1,5 kW 400°/2h	960	27000
AXV 900-9-6 - 3 kW 400°/2h	960	35000