



Characteristics



- External rotor motor protected through thermal contact
- 0-100% regulable speed
- Balanced according ISO1940
- Oversized ball bearings, lubricated for life, apt till -30°C
- Low noise level
- Inlet airflow way "V" or outlet "A", to choose
- 5 possible mountings: VRE without grille, VGR with flat grille, VPR with amb basket grille, VGV with tubular casing and VGC with square frame
- Other tensions and executions on request

Specifications

| Model | Tension (V (50 Hz)) | Current fans (A) | Power (W) | Speed (rpm) | Air Flow (m³/h) | Maximum Pressure (Pa) |
|-------------|---------------------|------------------|-----------|-------------|-----------------|-----------------------|
| 2VRE15-200 | 1x230V | 0,31 | 70 | 2485 | 950 | 150 |
| 2VRE25-250 | 1x230V | 0,47 | 106 | 2750 | 1510 | 250 |
| 2VRE45-300 | 1x230V | 0,79 | 181 | 2650 | 2625 | 300 |
| 2VREt25-200 | 3x400V | 0,16 | 71 | 2745 | 1040 | 260 |
| 2VREt35-250 | 3x400V | 0,18 | 93 | 2665 | 1535 | 225 |
| 2VREt45-300 | 3x400V | 0,33 | 168 | 2640 | 2550 | 300 |
| 4VRE15-200 | 1x230V | 0,14 | 32 | 1385 | 510 | 67 |
| 4VRE25-250 | 1x230V | 0,26 | 59 | 1390 | 1095 | 125 |
| 4VRE35-300 | 1x230V | 0,41 | 88 | 1320 | 1870 | 100 |
| 4VRE45-350 | 1x230V | 0,63 | 132 | 1280 | 2825 | 100 |
| 4VRE45-400 | 1x230V | 0,66 | 151 | 1165 | 3650 | 80 |
| 4VREt25-200 | 3x400V | 0,16 | 45 | 1475 | 530 | 86 |
| 4VREt25-250 | 3x400V | 0,18 | 69 | 1390 | 1145 | 120 |
| 4VREt35-300 | 3x400V | 0,21 | 99 | 1320 | 1845 | 130 |
| 4VREt45-350 | 3x400V | 0,33 | 120 | 1330 | 2835 | 155 |
| 4VREt45-400 | 3x400V | 0,36 | 162 | 1200 | 3765 | 140 |