



Characteristics



- Low height for false ceiling installation
- Forward curved impellers balanced statically and dynamically according to ISO 1940, class G 2,5
- External rotor motor protected through thermal contact
- 0-100% variable speed
- Mounting in any position
- WS = Sound Absorbing Casing
- EX reference = ATEX

Specifications

Model	(V (50 Hz))	(A)	(kW)	(rpm)	(m³/h)	(Pa)
EKAD 200-4*	No ERP					
EKAD 200-4 EX	No Apply					
EKAD 225-4 EX	No Apply					
EKAD 225-4K*	No ERP					
EKAD 250-4*	No ERP					
EKAD 250-4 EX	No Apply					
EKAD 250-4.5FA	ERP 2018					
EKAD 280-4*	No ERP					
EKAD 280-4 EX	No Apply					
EKAD 280-4.6FA	ERP 2016					
EKAD 280-4K*	No ERP					
EKAD 280-6*	No ERP					
EKAD 280-6 EX	No Apply					
EKAD 315-4 EX	No Apply					
EKAD 315-4.6HF	ERP 2018					
EKAD 315-6*	No ERP					
EKAD 315-6 EX	No Apply					
EKAD 355-4*	No ERP					
EKAD 355-4.7KF	ERP 2016					
EKAD 355-6 EX	No Apply					
EKAD 355-6K*	No ERP					
EKAD 400-4.7NA	ERP 2016					
EKAD 400-6.7KF	ERP 2018					
EKAD 400-8.7HA	ERP 2016					
EKAD 450-6.7NA	ERP 2016					
EKAD 450-8.7KF	ERP 2016					
EKAE 200-2 *	No ERP					
EKAE 200-4*	No ERP					
EKAE 225-4*	No ERP					
EKAE 225-4K*	No ERP					
EKAE 250-4*	No ERP					
EKAE 250-6*	No ERP					
EKAE 280-4*	No ERP					
EKAE 280-6K*	No ERP					
EKAE 315-6K*	No ERP					

* Only available outside the EU, inside the EU valid as a spare part