



Characteristics



- EC Motor of low consume protected through thermal contact with electrical regulation integrated
- Variable speed with signal 0-10V or 4-20 mA
- Backward curved impellers balanced statically and dynamically according to ISO 1940, class G 2,5
- Low height for false ceiling installation
- Some models available with acoustic insulation. Consult
- WS = Sound Absorbing Casing

Specifications

Model	(V (50 Hz))	(A)	(kW)	(rpm)	(m³/h)	(Pa)
KHAG 225.3BK W	ERP 2018					
KHAG 250.3DE W	ERP 2018					
KHAG 280.4EA W	ERP 2018					
KHAG 280.4EA WS	ERP 2018					
KHAG 315.4EA W	ERP 2018					
KHAG 315.4EA WS	ERP 2018					
KHAG 315.5FA W	ERP 2018					
KHAG 315.5FA WS	ERP 2018					
KHAG 355.4EA W	ERP 2018					
KHAG 355.4EA WS	ERP 2018					
KHAG 355.5FA W	ERP 2018					
KHAG 355.5FA W-3	ERP 2018					
KHAG 355.5FA WS	ERP 2018					
KHAG 355.5FA WS-3	ERP 2018					
KHAG 400.5FA W	ERP 2018					
KHAG 400.5FA W-3	ERP 2018					
KHAG 400.5FA WS	ERP 2018					
KHAG 400.5FA WS-3	ERP 2018					
KHAG 450.5FA W	ERP 2018					
KHAG 450.5FA WS	ERP 2018					
KHAG 450.5HF W	ERP 2018					
KHAG 450.5HF WS	ERP 2018					
KHAG 500.6FF W	ERP 2018					
KHAG 500.6FF WS	ERP 2018					
KHAG 560.6IF W	ERP 2018					
KHAG 560.6IF WS	ERP 2018					