




Characteristics



- Casing made of extruded aluminium of triple chamber
- Casing made from galvanized steel sandwich type with internal fiberglass insulation 20 mm thick
- Belt driven motors normalized IEC to be calculated depending on the working point Low noise level Special Special executions and higher capacity on request
- Versions:
  - TRZ Models with forward curved impellers
  - HRZ Models with backward curved impellers

Specifications

Model	(m <sup>3</sup> /h)	(kW)
AIRBOX 100 HRZ 355	-	
AIRBOX 100 HRZ 400	-	
AIRBOX 100 TRZ 355	-	
AIRBOX 100 TRZ 400	-	
AIRBOX 127 HRZ 200	-	
AIRBOX 127 HRZ 450	-	
AIRBOX 127 TRZ 450	-	
AIRBOX 127 TRZ 500	-	
AIRBOX 150 HRZ 560	-	
AIRBOX 150 HRZ 630	-	
AIRBOX 150 TRZ 560	-	
AIRBOX 150 TRZ 630	-	
AIRBOX 50 HRZ 180	-	
AIRBOX 50 HRZ 200	-	
AIRBOX 50 TRZ 180	-	
AIRBOX 50 TRZ 200	-	
AIRBOX 67 HRZ 225	-	
AIRBOX 67 HRZ 250	-	
AIRBOX 67 TRZ 225	-	
AIRBOX 67 TRZ 250	-	
AIRBOX 80 HRZ 280	-	
AIRBOX 80 HRZ 315	-	
AIRBOX 80 TRZ 280	-	
AIRBOX 80 TRZ 315	-	