



Característiques



- Bastidor rígid de poliestilè
- Mitja filtrant de fibra de vidre plegada amb el sistema 'mini-pleat'
- Filtre anticorrossiu i completament incinerable

Especificacions

| Model        | Dimensions<br>(mm) | Eficiència EN 779 / EN 1882 | Cabal<br>(m³/h) | Presió Inicial<br>(Inc. Pa) |
|--------------|--------------------|-----------------------------|-----------------|-----------------------------|
| D10 12X24X12 | 287x592x292        | H10                         | 1450            | 170                         |
| D10 20X24X12 | 490x592x292        | H10                         | 2450            | 170                         |
| D10 24X24X12 | 592x592x292        | H10                         | 3000            | 170                         |
| D13 12X24X12 | 287x592x292        | H13                         | 1450            | 250                         |
| D13 20X24X12 | 490x592x292        | H13                         | 2450            | 250                         |
| D13 24X24X12 | 592x592x292        | H13                         | 3000            | 250                         |
| D7 12X24X12  | 289x592x292        | F7                          | 2100            | 125                         |
| D7 20X24X12  | 490x592x292        | F7                          | 3400            | 125                         |
| D7 24X24X12  | 592x592x292        | F7                          | 4250            | 125                         |
| D9 12X24X12  | 287x592x292        | F9                          | 2100            | 160                         |
| D9 20X24X12  | 490x592x292        | F9                          | 3400            | 160                         |
| D9 24X24X12  | 592x592x292        | F9                          | 4250            | 160                         |