



Characteristics



- Universal shaded ring motor
- Bronze auto-lubricated bearings
- Low noise level
- Intermediate dimensions optional
- Some models require a minimum quantity purchasing order

Specifications

| Model              | Tension<br>(V (50 Hz)) | Current fans<br>(A) | Power<br>(W) | Speed<br>(rpm) | Air Flow<br>(m³/h) | Maximum Pressure<br>(Pa) |
|--------------------|------------------------|---------------------|--------------|----------------|--------------------|--------------------------|
| FCL 60/120/M25     | 1x230V                 | 0,19                | 10           | 2300           | 130                | 45                       |
| FCL 60/180/M25     | 1x230V                 | 0,19                | 10           | 2300           | 176                | 48                       |
| FCL 60/180+180/M38 | 1x230V                 | 0,26                | 15           | 2400           | 252                | 47                       |
| FCL 60/240/M38     | 1x230V                 | 0,26                | 15           | 2400           | 223                | 47                       |
| FCL 60/240+240/M38 | 1x230V                 | 0,26                | 15           | 2400           | 288                | 44                       |
| FCL 60/300/M38     | 1x230V                 | 0,26                | 15           | 2400           | 274                | 48                       |
| FCL 60/300+300/M38 | 1x230V                 | 0,26                | 15           | 2400           | 306                | 44                       |
| FCL 60/360/M38     | 1x230V                 | 0,26                | 15           | 2400           | 270                | 51                       |
| FCL 60/360+360/M38 | 1x230V                 | 0,26                | 15           | 2400           | 349                | 40                       |
| FCL 60/420/M38     | 1x230V                 | 0,26                | 15           | 2400           | 295                | 54                       |
| FCL 60/420+420/M38 | 1x230V                 | 0,26                | 15           | 2400           | 378                | 40                       |