



Characteristics



- Casing made of extrusioned aluminium
- Panels made of galvanized steel with internat insulation 25 mm thick
- Controller and speed regulation included , with 5-speed selection and 20 m of telephonic cable with fast connectors RJ45
- Optional automatic regulation depending on the temperature, sloping of the premises, etc.
- Compatibles with BMS
- On request: with prefilter at the inlet mounted inside the unit

Specifications

Model	Tension (V (50 Hz))	Current fans (A)	Power fans (kW)	Speed (rpm)	Air Flow (m³/h)	Maximum Pressure (Pa)
VARIAIRBOX 43-7/74	1x230V	1,4	0,32	1080	1700	280
VARIAIRBOX 43-7/76	1x230V	0,75	0,17	760	1450	125
VARIAIRBOX 43-7/94	1x230V	2,6	0,57	1240	3000	260
VARIAIRBOX 43-7/94K	1x230V	2	0,44	1050	2700	260
VARIAIRBOX 54-9/94	1x230V	3,9	0,87	950	3600	360
VARIAIRBOX 54-9/96	1x230V	1,6	0,36	660	2600	170
VARIAIRBOX 64-10/104	1x230V	4,8	1,1	1050	4200	500
VARIAIRBOX 64-10/106	1x230V	2,8	0,6	875	4000	250
VARIAIRBOX 77-12/126	1x230V	5,2	1,15	820	5700	340