



Characteristics



- Directional rotation selector
- Universal flange for shifts Ø6 to Ø16 mm and square from 5 to 12 mm
- Models L...C of quick running
- For shutters till 1m², depending on manufacturer

Specifications

| Model | Torque (Nm) | Tension (V (50 Hz)) | Control | Running Time 90° (s) | Auxiliar Contact | Feedback signal (kOhm) |
|----------|-------------|---------------------|---------|----------------------|------------------|------------------------|
| L 230 | 5 | 230AC | T/N | 80 -150 | - | - |
| L 230 C | 5 | 230AC | T/N | 20 - 35 | - | - |
| L 230 CP | 5 | 230AC | T/N | 20 - 35 | - | 10 |
| L 230 CS | 5 | 230AC | T/N | 20 - 35 | 1x3A | - |
| L 230 P | 5 | 230AC | T/N | 80 -150 | - | 10 |
| L 230 S | 5 | 230AC | T/N | 80 -150 | 1x3A | - |
| L 24 | 5 | 24AC/DC | T/N, 3P | 80 -150 | - | - |
| L 24 C | 5 | 24AC/DC | T/N, 3P | 20 - 35 | - | - |
| L 24 CP | 5 | 24AC/DC | T/N, 3P | 20 - 35 | - | 10 |
| L 24 CR | 5 | 24DC | 0,,,10V | 20 - 35 | - | - |
| L 24 CS | 5 | 24AC/DC | T/N, 3P | 20 - 35 | 1x3A | - |
| L 24 P | 5 | 24AC/DC | T/N, 3P | 80 -150 | - | 10 |
| L 24 R | 5 | 24DC | 0,,,10V | 80 -150 | - | - |
| L 24 S | 5 | 24AC/DC | T/N, 3P | 80 -150 | 1x3A | - |