



## Characteristics



- Plastic casing PE, PP on request
- Backward curved impeller in plastic PP balanced statically and dynamically
- Three phase motors standard IEC
- In belt driven models, motor to be calculated depending on the point of work
- EEx Execution "e" or "d", on request
- 16 possible orientations

## Specifications

Model	(W)	(rpm)	(m <sup>3</sup> /h)	(Pa)
EPND 160-2	470			
EPND 160-4	130			
EPND 160-T	1500			
EPND 200-2	750			
EPND 200-4	165			
EPND 200-T	1500			
EPND 225-2	1000			
EPND 225-4	240			
EPND 225-T	1800			
EPND 250-2	1300			
EPND 250-4	300			
EPND 250-T	1800			
EPND 280-2	1700			
EPND 280-4	380			
EPND 280-T	1700			
EPND 315-4	520			
EPND 315-T	1470			
EPND 355-4	650			
EPND 355-T	1800			
EPND 400-4R	885			
EPND 400-6R	380			
EPND 400R-T	3100			
EPND 450-4R	1150			
EPND 450-6R	490			
EPND 450R-T	3950			
EPND 500-4R	1430			
EPND 500-6R	620			
EPND 500R-T	4250			
P71 RT	3760			
P714R	1700			
P80 RT	4000			
P804R	2650			
P90 RT	4150			
P904R	3200			