



Characteristics



- PE or PP casing and fiberglass
- Simple inlet centrifugal impeller in injected plastic PP
- Three phase motors standard IEC, type B5
- Single phase motor optional
- Execution EEx "e" o "d", on request

Specifications

| Model | Tension (V (50 Hz)) | Current fans (A) | Power fans (kW) | Speed (rpm) | Air Flow (m ³ /h) | Maximum Pressure (Pa) |
|-------------|------------------------|---------------------|--------------------|----------------|---------------------------------|--------------------------|
| FC-AC 250-4 | 3x400V | 0,46 | 0,09 | 1400 | 1000 | 160 |
| FC-AC 315-4 | 3x400V | 0,76 | 0,25 | 1400 | 1800 | 240 |
| FC-AC 315-6 | 3x400V | 0,81 | 0,18 | 900 | 1150 | 100 |
| FC-AC 355-4 | 3x400V | 1,35 | 0,37 | 1400 | 2700 | 330 |
| FC-AC 355-6 | 3x400V | 0,81 | 0,18 | 900 | 1700 | 140 |
| FC-AC 400-4 | 3x400V | 1,6 | 0,55 | 1400 | 4000 | 460 |
| FC-AC 400-6 | 3x400V | 1,95 | 0,25 | 900 | 2650 | 190 |
| FC-AC 450-4 | 3x400V | 3,15 | 1,1 | 1400 | 5600 | 600 |
| FC-AC 450-6 | 3x400V | 1,35 | 0,37 | 900 | 3700 | 250 |